



PRODUCT FEATURES

- 1/4 HP Induction built motor
- Gear driven permanently lubricated transmission
- Heat-treated hardened steel alloy gears and shafts
- Three fixed speeds
- Thermal overload protection
- Rigid cast aluminum body
- 8 litre stainless steel bowl
- Polycarbonate bowl safety guard
- Safety interlocked bowl lift
- Front mounted controls
- 15 minute digital timer
- Overload reset button for motor protection
- White with gold epoxy enamel finish
- 1.8m cord and plug

STANDARD ACCESSORIES

- 8 litre bowl (stainless steel) Ref # SP800A-30
- Beater (aluminium) Ref # SP800A-25
- Whisk (stainless steel) Ref # SP800A-27
- Dough hook (aluminium) Ref # SP800A-26A
- Bowl safety guard (polycarbonate) Ref # SP800A-154

OPTIONAL ACCESSORIES

- Bowl safety guard (stainless steel) Ref # 800155-SUS

TECHNICAL DATA

Power	200 Watts	1/3 HP
Electrical data	230V/50/1	Draw 1.6 Amp
	Single phase - plug supplied	
Speed	3 speed - 132 / 235 / 421 rpm	
Dimensions (LxWxH)	442 x 346 x 579 mm	
Gross weight	25 kg	
Reference	SP800A-C	

STANDARDS

